

EP-07

Magnetic ground blocks for welding



COD	MOD	Ø	Kg	Resist.	
29006	MG 1	6 cm	0,18	150 A	
29007	MG 2	9 cm	0,55	300 A	6

Main features:

For industrial use:

- Model MG1 up to 150 Amps
- Model MG2 up to 300 Amps
- Permanent ferrita magnet

Materials and Finishing:

- Total diameter: 5.7 cm in model MG1 and 8.8 cm. In MG2
- Steel sheet outer body 2.5mm thick for MG2 . 2mm for MG1
- Permanent ferrita magnet glued to the main steel body with a highly resistant epoxy resin
- Diameter for MG2 ext 70 / int 32mm x 15mm
For MG1 , ext 45/ int 22mm x 8mm
- Brass screws with stamped half inch head x19mm in MG2 and 5/16" X 12.5mm in MG1,
- Two zinc coated steel nuts, two brass washers 25mm for MG2 and 23mm for MG1
- Two insulator washers in MG2 and one embedded in the main body for MG1
- Thermally treated 4 ringed steel spring of 0.5 mm for MG1 and 1.2mm for MG2

Packing and labelling:

Individual blister pack

How to use instructions on blister card

Boxes of 10 pieces

EAN- 13 code



Rulings

Manufactured in Taiwan .

The articles are vigorously tested in our quality control department to ensure maximum product guarantee by carrying out all necessary tests

No special safety ruling applied

Industrias Piqueras works following ISO 9001 and ISO 14001 quality standards